

# RoadQuake<sup>®</sup> 2F

## TEMPORARY PORTABLE RUMBLE STRIP

Designed to reduce accidents and save lives, RoadQuake 2F TPRS alerts distracted drivers to changing road conditions, like work zones and check points.



**Ideal for Work Zones where daily installation and removal is required.**



**RoadQuake 2F TPRS features a convenient, one-piece, folding design.**



Folds for easy storage and transportation

### **RoadQuake TPRS is:**

**Temporary** - No nails or glue are needed for installation and use. Quick installation and removal, and no clean-up.

**Portable** - No installation equipment needed. A crew of 2 can install an array in minutes.

**Durable** - 3-5 year life under normal conditions.

Suitable for use in rain and temperatures of 0 °to 180 °F and in speeds up to 80 mph.

RQ TPRS meets Section 6F.87 of the *MUTCD*, 2009 Edition.



Unfolds for easy deployment

# RoadQuake® 2F TPRS

## FEATURES AND SPECIFICATIONS



RoadQuake 2F TPRS alerts distracted drivers to changing road conditions, like work zones or check-points.

### RoadQuake 2F TPRS Features:

- Meets Section 6F.87 of the *MUTCD*, 2009 Edition.
- Generates the same level of sound and vibration as milled strips.
- For posted speed limits up to 80 mph and temperatures from 0° to 180° F.
- 13" W x 3/4" H x 132" L, when unfolded. Covers an entire lane.
- Folds to a compact 66" length. Weighs 110 lbs.
- Ergonomic handles make installation and storage easy. Non-slip textured surface helps to keep RoadQuake 2F TPRS in place.
- Bevels on both sides take the guess-work out of installation.
- Hinge links meet ANSI Standard for master chain link, size 60-2.

US Patent No. 7,736,087. Other Patents Pending.



Deployment and removal of an array can be a one person job using the RoadQuake 2F CRIB® Cargo Carrier.