

TRAFFIC CONES

Standard, Trimline, Recessed Collar

Work Area Protection has been a leading manufacturer of high-quality traffic cones for over 50 years. Work Area Protection cones are used every day, all over the world. These cones are designed and manufactured to last for years. Your safety demands it and Work Area Protection delivers it with high-visibility, durable, high-quality traffic cones.

Features

- One-piece, flow-molded polyvinyl chloride
- · Anti-fade, fluorescent orange color
- Permanent stenciling available
- Broad base for stability
- Heat resistance to 160°
- Elongation: 200%
- · Tensile strength: 1200 psi minimum
- Hardness: 80±5 conical, 75±5 base
- Tear strength: 250 psi
- Meet NCHRP350 requirements
- Meet MUTCD and FHWA requirements

STANDARD TRAFFIC CONES

Product No.	Model No.	Description	Top Thickness	Bottom Thickness	A	В	С	D	Cone Height	Weight Lbs.		Pallet Oty. n (Cartons)	Pallet Oty. (Loose))	
271449	6PVCS	Standard	.056"	.090"	4-1/2"	-	7/8"	2-1/4"	6"	1/4	200	N/A	N/A	
271452	12PVCS	Standard	.065"	.120"	8-1/4"	1-1/4"	2-3/16"	6-1/2"	12"	1-1/2	30	480	1000	
271456	18PVCS	Standard	.065"	.120"	11-3/8"	1-1/4"	2-3/16"	7-1/4"	18"	3	20	240	750	
271453	18PVCH	Heavy	.070"	.125"	11-3/8"	1-1/4"	2-3/16"	7-1/4"	18"	4	20	240	500	
271459	18PVCX	Extra Heavy	.080"	.125"	13"	1-1/4"	2-3/16"	7-1/4"	18"	7	14	168	300	
271469	28PVCS	Standard	.075"	.130"	15-1/4"	1-1/4"	2-3/16"	10-1/2"	28"	7	10	90	250	
271461	28PVCH	Heavy	.080"	.135"	15-1/4"	1-1/4"	2-3/16"	10-1/2"	28"	10	10	90	200	
271486	28PVCX	Extra Heavy	.075"	.130"	15"	1-1/4"	2-1/2"	10-1/2"	28"	12	10	90	200	
271494	36PVCS	Standard	.075"	.130"	15"	1-1/4"	2-1/2"	10-1/2"	36"	10	10	90	200	
271488	36PVCH	Heavy	.075"	.130"	15-1/2"	1-1/4"	2-1/2"	10-1/2"	36"	12	9	81	200	


Based on Pallet: 45" x 45"

A = Base size (square)

B = Hole diameter at top

C = Cone diameter at top

D = Cone diameter at base



Standard 28" Cone with 6" & 4" Reflective Collars

Available plain or with reflective collars attached